

MEGA PRO

Ribbed Roof Panel



▲ Wall Application

▼ Roof Application



Specifications

Length:	Maximum of 53'
Width:	★ 39 3/8" - (1000mm)
Thickness:	2" 2 1/2" 3" 4" 5" 6" 8"
Foam Core:	PUR, PIR, PIR R+
Joint Type:	Tongue and Groove - Exposed
Gasket:	Open Cell Gasket - <i>Butyl available upon request</i>
Steel Gauge:	External: 22, 24, 26 - Internal: 22, 24, 26, 28
Coating:	Polyester Std. G60, Kynar G90

Features

Adouble-steel sheet roof panel, insulated with rigid foam. This design caters to 2% min slope roofs. External face with 4 trapezoidal rows to enhance static and dynamic forces. Exposed fastening system that includes saddle clips and cap ribs for concealed fastening and weather tightness. Applicable with several roofing sub-structures.

Options

Especially suited for use in industrial, warehouses, and residential construction. Versatility, load resistance and easy installation make MEGA PRO a reliable solution, from new construction to roof refurbishing. Available with butyl seal placed in plant.

Benefits

- Rust resistance
- High mechanical strength
- Hygienic and easy wash material - Mold and humidity resistance - Gasket barrier to prevent vapor leaks

Suitable for

- Industrial:** Warehouse, Distribution Centers, Data Centers
- Cold Chain:** Cold Storage, Food Processing
- Commercial:** Office, Retail, Convention Centers
- Architectural:** Schools, Museums, Government, Residential
- Specialized:** Airports, Green Building, Grain Sheds

